

## *Specification*

### Cable Assembly with RF Connectors

1. Model No.:201-216
2. Frequency: 1~3 GHz
3. VSWR: 2.0:1
4. Cable: RG-316
5. Cable's color: Black
6. Connector: FME M S type & RA SMB F

*✧RoHS Compliant*

*✧ISO 9001 & ISO 14001*

Cable	RG316/U	1Pc/1PE bag, 10Pcs/1PE bag	<div style="border: 1px solid black; padding: 5px; display: inline-block;"> <b>ROHS</b>          ISO 9001          ISO 14001       </div>
OD	∅2.6±0.1mm		
Cover	Black		
FME M S	Ni-plated		
RP SMB M RA	Gold-plated		

  

Unit packaging sticker

10Pcs packaging sticker

10Pcs packaging PE bag

Unit packaging PE bag

Material:		Treatment:		TRANSVOICE			
Drawer	Design	Approv	Tolerance	Unit:		TITLE	FME M S
			X=±0.5	mm			SMB-316U
			X=±0.2	Ver: A	Scale: 1:1	Model NO	+RP SMB M RA
			XX=±0.1	File NO	QR0402	Drawing NO	201-216
			XXX=±0.05				100-27001-084

NO	DESCRIPTION	MATERIAL / FINISH	Q'TY
Part NO	CX-SMB316FME-2033D		

Frequency (MHz)	VSWR	Insertion Loss (dB)
900 MHz	1.18	-0.60
1800 MHz	1.59	-1.12
2100 MHz	1.63	-1.26
2400 MHz	1.84	-1.48
3000 MHz	2.34	-1.97

# Test Report

